Mc MINING GROUPE PICHORI Quality First

LEADER IN INDUSTRIAL TOOLS & EQUIPMENT

Technical sheet



Hammer Drill - D25501K-QS SDS-Max Combination Hammer Drill

Marque: DEWALT

Ref Product: wire:D25501K-QS

Ref Mcmining: DEWALTD25501K-QS

DESCRIPTION	
	- Ideal for drilling anchor fixing and through holes in concrete and masonry from 12 to 40 mm in diameter. Core drilling up to 90 mm - Chain drive improves durability and increases efficiency together with an oil filled gearbox to ensure total component lubrication and superior heat dissipation - Ergonomic, compact and slim line design maximises control and offers easy access to confined spaces - Excellent power to weight ratio: 11 Joules of impact energy delivered by a 6.1 kg hammer - Rotation-stop for medium-light demolition applications - Unique dust sealing protection to prevent even the finest dust ingress into the hammer mechanism delivering high durability and extended tool life - Hammer mechanism is optimised by reducing the number of components and by improving dampening to deliver maximum impact energy and therefore the efficiency to drill into the hardest concrete - Efficient mechanism delivers impact blows directly to the bit without losses through excessive vibration and rebound dampening reduces stress to the tool - Soft rubber grip handles improve user comfort lowering fatigue during extended use - STANDARD - Multi-position side handle with depth stop - Heavy duty carrying case
SPECIFICATIONS	
	- Power Input : 1100 Watts - Power Output : 500 Watts - Load Speed : 400 rpm - Blows per Minute : 2740 bpm - Impact Energy : 11 J - Tool Holder SDS-Max Morse Taper - Max. Drilling Capacity [Concrete] : 40 mm - Max. Drilling Capacity [Breakthrough bit] : 55 mm - Max. Drilling Capacity [Core bit] : 90 mm - Weight : 6.15 kg - Length : 457 mm - Height : 245 mm - Width : 104 mm - Hand/Arm Vibration : 18.3 m/s2 - Uncertainty K 1 (Vibration) : 1.8 m/s² - Hand/Arm Vibration - Chisel : 13.2 m/s² - Uncertainty K 2 (Vibration) : 1.6 m/s² - Sound Pressure : 94 dB(A) - Uncertainty K 1 (Sound) : 3 dB(A) - Accoustic Pressure : 104 dB(A) - Uncertainty K 2 (Sound) : 3 dB(A)
BRAND	**DEWALT**