Mc MINING GROUPE PICHORI Quality First

LEADER IN INDUSTRIAL TOOLS & EQUIPMENT

Technical sheet



Hammer drill - 48 mm SDS-Max Combination Hammer

Marque: DEWALT

Ref Product: wire:D25711K-GB

Ref Mcmining: DEWALTD25711K-GB

DESCRIPTION	
	Ideal for drilling anchor fixing and through holes in concrete and masonry from 12 to 48 mm in diameter. Core drilling up to 115 mm. Active Vibration Control system incorporating a floating handle delivers extremely low vibration. Electronic variable speed and impact energy control.
SPECIFICATIONS	
	- SPECIFICATION: Power Input: 1250 Watts - Power Output: 840 Watts - Load Speed: 132-265 rpm - Blows per Minute: 1225-2450 bpm - Impact energy (EPTA 05/2009): 9 J - Tool Holder SDS-Max - Max. Drilling Capacity [Concrete]: 48 mm - Max. Drilling Capacity [Breakthrough bit]: 80 mm - Max. Drilling Capacity [Core bit] : 115 mm - Weight: 8.7 kg - Length: 528 mm - Height: 268 mm - Width: 116 mm - Hand/Arm Vibration: 8.9 m/s2 - Uncertainty K 1: (Vibration): 1.5 m/s² - Hand/Arm Vibration - Chisel : 8.1 m/s² - Uncertainty K 2 (Vibration) : 1.5 m/s² - Sound Pressure: 96 dB(A) - Uncertainty K 1 (Sound): 3 dB(A) - Accoustic Pressure: 107 dB(A) - Uncertainty K 2 (Sound): 3 dB(A)
BRAND	**DEWALT**