LEADER IN INDUSTRIAL TOOLS & EQUIPMENT

Technical sheet



Salvage Drums - Poly-Overpack® 95 Salvage Drum

Marque: ENPAC

Ref Product: wire:1237-YE

Ref Mcmining: EN1237-YE

Description	
Our Poly-Overpack® 95 meets Group 1 packaging standards and salvage drum regulations. Unlike competing overpacks, Our Poly-Overpack® 95 safely contains a wide range of hazardous materials including: acids, corrosives and damaged parts—in 55-gallon drums.	
Specifications	
Tight, secure and leak-free container closing is simple: place any long object (like a wooden two-by-four) in the handy lid slots, and turn to screw the lid down tightly. - Meets performance-oriented packaging requirements of U.S. DOT and UN regulations. - Twist-down lid for safe closure. - Closed cell gasket in lid seals closure. - Castellations in lid allow for easy closing with pole or wooden 2x4” - Double wall lid gives added strength. - Molded area allows or easy gripping and lifting by material handling equipment. - Ribbed design provides extra strength. - 100% UV-protected polyethylene provides protection over a wide range of chemicals. Available in up to 100% recycled material, ECO-Efficient edition	
Top Diameter External:	31.9 in. / 80 cm.
Top Diameter Internal:	27 in. / 69 cm.
Bottom Diameter External:	25.75 in. / 65 cm.
Bottom Diameter Internal:	24.75 in. / 63 cm.
Height Internal:	41.5 in. / 105 cm
Height External:	37 in. / 94 cm.
Weight:	48.2 lbs. / 21.9 kg.
Load Capacity:	650 lbs. / 295 kg.
Spill Capacity:	95 gal. / 359.6 L
Regulations:	**UN 1H2/X295/S** **DOT 49 CFR 173.3**