LEADER IN INDUSTRIAL TOOLS & EQUIPMENT

# Technical sheet




**Striking box wrench 12 points 27 mm AH0027A AlBz- DIN7444**

Marque: AMPCO

Ref Product: wire:AH0027A

Ref Mcmining: PRAH0027A-AM

| **Description** |
|---|
| Ampco non-sparking products are intended for use in areas where a high risk of fire or explosion exists,as in the presence of flammable gases or liquids.Non-magnetic Ampco tools are recommended in military applications,Â mine clearance operations and in the medical field, for MRI and other scanning equipment or equipment using large magnets. Outstanding corrosion resistance also make Ampco tools the professional's choice in the most demanding and aggressive environments,on land or water. |
| Box wrenches in the regular pattern are designed for general service. The Heavy- Duty and Striking Face patterns are designed for the service indicated. The Electronic Hex Box patterns are designed for the lighter service encountered in electronic, carburetor and ignition work. Ratcheting Box and split box wrenches are for light duty and should not be used in heavy-duty applications. |
| Never use a hammer on any wrench other than a Striking Face wrench. Use a sledge type hammer.Never use an extension on the wrench handle. |
| **Certifications** |
| - **ISO9001**<br><br>AMPCO SAFETY TOOLS Aluminum Bronze (AlBz) alloy helps fulfill the recommendation in:<br><br>- **European ATEX directive** for working in Zones 0 and/or 20 of all explosion groups.<br><br>- **BAM (FEDERAL INSTITUTE FOR MATERIALS RESEARCH AND TESTING, Berlin Germany) Standard operating procedure "QMH-NEG-005"** "StAA zur Schlagfunkenprüfung von Werkstoffpaarungen" dated 2012-03-01 : non-sparking tools made of these materials are appropriate for use in potentially explosive atmospheres of zone 0, 1, 2 and 20, 21, 22 according to directive **1999/92/EC** of all explosion groups according to **IEC 60079-20-1:2010**.<br><br>- **EN 1127-1 and EN 13463-1** |
| **Specification** |

| **REF** | **s mm** | **l mm** | **g** | | |
|---|---|---|---|---|---|
| AH0027A | 27 | 180 | 350 | | |