Mc MINING GROUPE PICHORI Quality First

LEADER IN INDUSTRIAL TOOLS & EQUIPMENT

Technical sheet



ELINGUE SANGLE DOUBL,D. 30-300mm, COEF.1/7, L: 1-10m, CMU:1-10T

Marque: LEVAC - FRANCE

Ref Product: wire:4822

Ref Mcmining: SANGW----------

DESCRIPTION					
ÉLINGUE SANGLE DOUBLE POLYESTER - 2 Boucles restreintes - Reference : 4822 Elingue sangle double : - 2 boucles restreintes Sangle tissée en polyester traitée anti-abrasion Très grande résistance aux hydrocarbures Coefficient de sécurité 7/1 Boucles renforcées					
SPECIFICATIONS TECHNIQUES					
Ref:	**Matière dominante :**	**CMU* (kg) :**	**Largeur de sangle (mm) :**	**Longueur (m) :**	**REF MC MINING :**
4822A20	Polyester	1000	30	2	**SANGW1TX2M-LEVAC**
4822A30	Polyester	1000	30	3	**SANGW1TX3M-LEVAC**
4822B10	Polyester	2000	60	1	**SANGW2TX1M-LEVAC**
4822B20	Polyester	2000	60	2	**SANGW2TX2M-LEVAC**
4822B30	Polyester	2000	60	3	**SANGW2TX3M-LEVAC**
4822B40	Polyester	2000	60	4	**SAMGW2TX4M-LEVAC**
4822B80	Polyester	2000	60	8	**SANGW2TX8M-LEVAC**
4822C20	Polyester	3000	90	2	**SANGW3TX2M-LEVAC**
4822C30	Polyester	3000	90	3	**SANGW3TX3M-LEVAC**
4822C40	Polyester	3000	90	4	**SANGW3TX4M-LEVAC**
4822C60	Polyester	3000	90	6	**SANGW3TX6M-LEVAC**
4822D30	Polyester	4000	120	3	**SANGW4TX3M-LEVAC**
4822D40	Polyester	4000	120	4	**SANGW4TX4M-LEVAC**
4822D60	Polyester	4000	120	6	**SANGW4TX6M-LEVAC**
4822D80	Polyester	4000	120	8	**SANGW4TX8M-LEVAC**
4822E30	Polyester	5000	150	3	**SANGW5TX3M-LEVAC**
4822E40	Polyester	5000	150	4	**SANGW5TX4M-LEVAC**
4822E50	Polyester	5000	150	5	**SANGW5TX5M-LEVAC**
4822E60	Polyester	5000	150	6	**SANGW5TX6M-LEVAC**
4822F30	Polyester	6000	180	3	**SANGW6TX3M-LEVAC**
4822F40	Polyester	6000	180	4	**SANGW6TX4M-LEVAC**
4822F60	Polyester	6000	180	6	**SANGW6TX6M-LEVAC**

4822F80	Polyester	6000	180	8	**SANGW6TX8M-LEVAC**
4822FA40	Polyester	8000	240	4	**SANGW8TX4M-LEVAC**
4822FA50	Polyester	8000	240	5	**SANGW8TX5M-LEVAC**
4822FA60	Polyester	8000	240	6	**SANGW8TX6M-LEVAC**
4822FA80	Polyester	8000	240	8	**SANGW8TX8M-LEVAC**
4822FA100	Polyester	8000	240	10	**SANGW8TX10M-LEVAC**
4822G60	Polyester	10000	300	6	**SANGW10TX6M-LEVAC**
4822G100	Polyester	10000	300	10	**SANGW10TX10M-LEVAC**
***CMU: Charge Maximale d'Utilisation**					