Mc MINING GROUPE PICHORI Quality First

LEADER IN INDUSTRIAL TOOLS & EQUIPMENT

Technical sheet



Goulotte 151 X150 WITH 120 CPVER

Marque: SCHNEIDER ELECTRIC

Ref Product: wire:SCETK15150

Ref Mcmining: SCETK15150

DESCRIPTION	
Goulotte 151 X150 WITH 120 CPVER(ETK15150)	
ETK15150	
Characteristics	Ultra - installation trunking - 151 x 50 mm - plastic - white - 2 m
Main Specifications	
Product or component type	Installation trunking
Colour tint	White - RAL 9010
Quantity per set	8 m
Type of packing	Protective foil
Compartment partitioning	1 compartment
Trunking dimension	151 x 50 mm
Device composition	Front cover
Trunking base	
Trunking material	Plastic
Front opening size	75 mm
Fixing mode	Screw-fixed
Pre-punched fixing	hole with distance of 230 mm between centers
Material	PVC (polyvinylchloride)
Length	2000 mm
height	151 mm
Width	50 mm
Environment	
Ambient air temperature for operation	-5...60 °C
Environmental health and issues	Cadmium free Lead free
IP degree of protection	IP40
IK degree of protection	IK07
Standards	**EN 50085-1 : 2005** **EN 50085-2-1 : 2006**
	RoHS (date code: YYWW) Compliant - since 1139 - Schneider Electric declaration of conformity