Mc MINING GROUPE PICHORI Quality First

LEADER IN INDUSTRIAL TOOLS & EQUIPMENT

Technical sheet



ABC dry chemical powder fire extinguishers 50KG

Marque: LX FIRE

Ref Product: wire:LX06-03

Ref Mcmining: LX06-03

Description	
ABC dry chemical powder fire extinguishers 50KG LX06-03	
ABC CHARACTERISTICS	ABC dry chemical powder fire extinguishers are suitable for use on : Class A (ordinary solids), Class B fires (flammable liquids) and Class C (gas and vapors) fires. The ABC type Portable Gas Cartridge Type fire extinguishers can also be used on electrically actuated fires.
PRODUCT FEATURES	- Easy and ergonomic during use - Fast and effective during extinguishing - Economical in maintenance and service - The shut-off valve with pressure indicator enhances extinguisher control - The valve design allows for temporary interruption during extinguishing - Refillable multiple times - The extinguisher tank is coated with UV-resistant polyester paint -
QUALITY AND SAFETY	The product is manufactured in compliance with international and EU market requirements, based on the ISO 9001 certified quality system. - It meets the requirements of the European standard EN3 and the Safety Directives PED 2014/68/EU. **CERTIFICATE N° :** **N°/15/CN/3808-6** **- N° /11/CN/2416-5** **- 06/03/2023** **- CE 0062** **- APRAGAZ B** **- EN 3-7** **- CE - EN1866-2 (2014)**
TECHNICAL SPECIFICATION	
DESCRIPTION	50KG ABC
CODE	LX06-03
AGENT	ABC DRY CHEMICAL POWDER 40
PROPELLANT	DRY AIR
MATERIAL	Q235B
VALVE	G2 PRESSURE RELIEF
WORKING PRESSURE	14bar at 20°C
MAX WORKING PRESSURE	18Bar

TEST PRESSURE	35Bar
FIRE CLASS	ABC
DISCHARGE TIME	>14s
EXTINGUISHER WEIGHT	77.22kg
OPERATING TEMPERATURE	-30°C - +60°C
CYLINDER SIZE (mm)	320x850
PACKING SZE (mm)	500x480x1150