Technical sheet



Safety Shower & Eye Washer Model:SS-S100

Marque:

Ref Product: wire:EXTDOUCSS-S100

Ref Mcmining: EXTDOUCSS-S100

Description	
The combination safety shower & eyewash unit saves space and fits easily into any work environment,allow workers to flush away hazardous substances that can cause injury. The shower valve operates quickly by a pull rod with a round handle. Shower provides a superior washdown with a more even spray pattern. Eyewash operated by a large, attractive push handle. safe, steady water flow under varying water supply conditions from 0.2-0.8 Mpa is assured by integral flow control valve assembly.	
Technical Details:?	
Material:	304 Stainless Steel
Shower Head/Bowl:	304 Stainless Steel
Shower Handle:	304 Stainless Steel
Spray Head:	ABS plastic in safety yellow color
Valve:	Shower valve is making of 1" SS ball valve. Eyewasher valve is making of 1/2"SS ball valve
Pedestal:	304 Stainless Steel
Foot treadle:	304 Stainless Steel
Flow Valve build in to avoid secondary hurt	
Water working pressure:	0.2MPA-0.8MPA
Flow control:	76L/Min
Standard:	**EN 15154-1&2:2006, AS 4775:2007, ANSI Z358.1-2014**
Gross Weight:	18.8KGS,Net Weight:17.5KGS
Dimension:	91cm*41cm*30cm