LEADER IN INDUSTRIAL TOOLS & EQUIPMENT

Technical sheet



Saw - 250 mm Combination Flip-Over Saw- 2000W

Marque: DEWALT

Ref Product: wire:DW743N-QS

Ref Mcmining: DEWALTDW743N-QS

DESCRIPTION	
	The classic TGS flip-over bevelling saw - Rapid tool free transformation from a saw bench to a mitre saw provides flexibility in a range of site and workshop applications - Handle mechanism allows the guard to retract automatically in mitre mode allowing safe and easy use - New high output heavy duty high torque induction motor provides years of maintenance free use, suitable for workshop applications where low noise characteristics are desirable - Three way extractor connection facility for efficient dust extraction - Integrated carry handles provide greater portability - Updated design for maximum cutting capacity across the range of mitre and bevel angles - Standard: 30 tooth SERIES 60® saw blade - Parallel fence - Push stick - 4 detachable legs - Saw blade guard - Assembly tool
SPECIFICATIONS	
	- SPECIFICATIONS - Power Input: 2000 Watts - Power Output: 1550 Watts - Blade Speed :2850 rpm - Blade Diameter: 250 mm - Blade Bore: 30 mm - Bevel Capacity: 45 ° - Max. Ripping Capacity [right] - Max. Ripping Capacity [left] - Max. Depth of Cut at 90º - Max. Depth of Cut at 45º - Weight: 37 kg - Depth:670 mm - Length :700 mm - Height: 750 mm - No Load Speed - Max. Crosscut Capacity at 90° - Max. Crosscut Capacity at 45° - Max. Depth of Cut [Saws] - Mitre Capacity [right/left]: 45 / 45 ° - Cutting Capacity at 90°/90°: (W x H) 180 × 20 mm - Cutting Capacity at 45°/90°: (W x H) 120 × 46 mm - Cutting Capacity at 90°/45°: (W x H) 150 × 20 mm - Max. Cutting Capacity at 45°/45°: - mm - Max. Cutting Capacity [Sawbench position 90°/90°]: 0 - 70 mm - Max. Cutting Capacity [Sawbench position 90°/45°]: 0 - 32 mm
BRAND	**DEWALT**