Mc MINING GROUPE PICHORI Quality First

LEADER IN INDUSTRIAL TOOLS & EQUIPMENT

# Technical sheet



**Hammer drill - 48 mm SDS-Max Combination Hammer**

Marque: DEWALT

Ref Product: wire:D25711K-GB

Ref Mcmining: DEWALTD25711K-GB

| DESCRIPTION | |
|---|---|
| | Ideal for drilling anchor fixing and through holes in concrete and masonry from 12 to 48 mm in diameter. Core drilling up to 115 mm. Active Vibration Control system incorporating a floating handle delivers extremely low vibration. Electronic variable speed and impact energy control. |
| **SPECIFICATIONS** | |
| | - SPECIFICATION:<br>Power Input: 1250 Watts<br>- Power Output: 840 Watts<br>- Load Speed: 132-265 rpm<br>- Blows per Minute: 1225-2450 bpm<br>- Impact energy (EPTA 05/2009): 9 J<br>- Tool Holder SDS-Max<br>- Max. Drilling Capacity [Concrete]: 48 mm<br>- Max. Drilling Capacity [Breakthrough bit]: 80 mm<br>- Max. Drilling Capacity [Core bit] : 115 mm<br>- Weight: 8.7 kg<br>- Length: 528 mm<br>- Height: 268 mm<br>- Width: 116 mm<br>- Hand/Arm Vibration: 8.9 m/s2<br>- Uncertainty K 1: (Vibration): 1.5 m/s²<br>- Hand/Arm Vibration - Chisel : 8.1 m/s²<br>- Uncertainty K 2 (Vibration) : 1.5 m/s²<br>- Sound Pressure: 96 dB(A)<br>- Uncertainty K 1 (Sound): 3 dB(A)<br>- Accoustic Pressure: 107 dB(A)<br>- Uncertainty K 2 (Sound): 3 dB(A) |
| | |
| **BRAND** | **DEWALT** |