Mc MINING GROUPE PICHORI
Quality First

LEADER IN INDUSTRIAL TOOLS & EQUIPMENT

Technical sheet



Hammer drill - 26mm SDS+ Hammer 800

Marque: DEWALT

Ref Product: wire:D25123K-QS

Ref Mcmining: DEWALTD25123K-QS

DESCRIPTION	
	- Ideal for drilling anchor and fixing holes into concrete and masonry from 4 to 26 mm in diameter - Impact-stop for drilling in wood, steel, ceramic and screwdriving applications - Rotation-stop for light chiselling applications in brick, soft masonry and occasionally concrete - Large 22 mm hammer mechanism delivers high performance with low stress to the critical components resulting in better durability - Electronic variable speed for total control in any application - Safety clutch eliminates sudden high-torque reaction should the bit jam - Ergonomic rubber coated back handle design for improved comfort in use - Rounded ergonomic industrial design allows easy and comfortable handling in any application - Improved sealing for maximum protection from dust ingress ensuring long tool life - Output air slots designed to protect users‘ eye Standard - Multi position side handle - Depth stop - Heavy duty carrying case
SPECIFICATIONS	
	Power Input : 800 Watts Power Output : 395 Watts No Load Speed : 0-1150 rpm Blows per Minute : 0-4300 bpm Impact energy (EPTA 05/2009) : 2.8 J Tool Holder : SDS-Plus Max. Drilling Capacity [Wood] : 30 mm Max. Drilling Capacity [Metal] : 13 mm Max. Drilling Capacity [Concrete] : 26 mm Max. Drilling Capacity [Core bit] : 65 mm Weight : 2.9 kg Length : 352 mm Height : 200 mm Hand/Arm Vibration - Drilling : 17.8 m/s² Uncertainty K 1 (Vibration) : 1.5 m/s² Hand/Arm Vibration - Chisel : 9.8 m/s² Uncertainty K 2 (Vibration) : 1.5 m/s² Hand/Arm Vibration - Metal : 2.6 m/s² Uncertainty K 3 (Vibration) : 1.5 m/s² Sound Pressure : 89 dB(A) Uncertainty K 1 (Sound) : 3.8 dB(A) Accoustic Pressure : 100.1 dB(A) Uncertainty K 2 (Sound) : 3.8 dB(A)
BRAND	**DEWALT**