Technical sheet



Hammer drill - 26mm L-Shape SDS - Combination Hammer with Quick Change Chuck Low

Marque: DEWALT

Ref Product: wire:D25324K-GB

Ref Mcmining: DEWALTD25324K-GB

Feature	
	Ideal for drilling holes and fixing anchors into concrete and masonry from 4 to 26 mm in diameter - Active Vibration Control system with floating handle delivers extremely low vibration and more comfort - SHOCKS - Active Vibration Control® Reduces vibration felt by the user at the handles. A Perform and Protect feature. - 8 amp motor provides high performance and overload protection: 0-1,150 RPM, 0-4,300 BPM - Rotation-stop for light chiselling applications in soft masonry and occasionally concrete - Impact stop and Quick Change Removable Chuck for precise drilling in wood and steel and screwdriving applications - Electronic variable speed for total control in any application - Impact-stop for drilling in wood, steel, ceramic and screwdriving applications - Mechanical clutch reduces sudden high-torque reaction should the bit jam - Ergonomic rubber coated back handle design for improved comfort in use - Connection for Integrated Dust Extraction System - Rounded ergonomic industrial design allows easy and comfortable handling - Improved sealing for maximum protection from dust ingress ensuring long tool life - Large 22 mm hammer mechanism delivers high performance with low stress to the critical components Standard Multi position side handle - Quick Adjustment depth stop - Quick Change 13 mm 3 Jaw Keyless Chuck for rotary drilling - Heavy duty carrying case
Specifications	

	Power Input: 800 Watts Abgabeleistung: 395 Watt No Load Speed: 0-1150 rpm Blows per Minute: 0-4300 bpm Impact energy (EPTA 05/2009): 2.8 J Tool Holder: SDS-Plus Max. Drilling Capacity [Wood]: 30 mm Max. Drilling Capacity [Metal]: 13 mm Max. Drilling Capacity [Concrete]: 26 mm Max. Drilling Capacity [Core bit]: 65 mm ´Gewicht: 3.5 kg Länge: 329 mm Height: 225 mm Hand/Arm Vibration - Drilling: 10.5 m/s² Uncertainty K 1 (Vibration): 1.5 m/s² Hand/Arm Vibration - Chisel: 10.5 m/s² Uncertainty K 2 (Vibration): 3.5 m/s² Hand/Arm Vibration - Metal: <2.5 m/s² Uncertainty K 3 (Vibration): 1.5 m/s² Sound Pressure: 85.4 dB(A) Uncertainty K 1 (Sound): 3.3 dB(A) Accoustic Pressure: 99.4 dB(A) Uncertainty K 2 (Sound): 3.3 dB(A)
Brand	**DEWALT**