LEADER IN INDUSTRIAL TOOLS & EQUIPMENT

# Technical sheet



**Salvage Drums - Poly-Overpack® 95 Salvage Drum**

Marque: ENPAC

Ref Product: wire:1237-YE

Ref Mcmining: EN1237-YE

| **Description** | |
|---|---|
| Our Poly-Overpack® 95 meets Group 1 packaging standards and salvage drum regulations. Unlike competing overpacks, Our Poly-Overpack® 95 safely contains a wide range of hazardous materials including: acids, corrosives and damaged parts—in 55-gallon drums. | |
| **Specifications** | |
| Tight, secure and leak-free container closing is simple: place any long object (like a wooden two-by-four) in the handy lid slots, and turn to screw the lid down tightly.<br>- Meets performance-oriented packaging requirements of U.S. DOT and UN regulations.<br>- Twist-down lid for safe closure.<br>- Closed cell gasket in lid seals closure.<br>- Castellations in lid allow for easy closing with pole or wooden 2x4”<br>- Double wall lid gives added strength.<br>- Molded area allows or easy gripping and lifting by material handling equipment.<br>- Ribbed design provides extra strength.<br>- 100% UV-protected polyethylene provides protection over a wide range of chemicals.<br>Available in up to 100% recycled material, ECO-Efficient edition | |
| | |
| Top Diameter External: | 31.9 in. / 80 cm. |
| Top Diameter Internal: | 27 in. / 69 cm. |
| Bottom Diameter External: | 25.75 in. / 65 cm. |
| Bottom Diameter Internal: | 24.75 in. / 63 cm. |
| Height Internal: | 41.5 in. / 105 cm |
| Height External: | 37 in. / 94 cm. |
| Weight: | 48.2 lbs. / 21.9 kg. |
| Load Capacity: | 650 lbs. / 295 kg. |
| Spill Capacity: | 95 gal. / 359.6 L |
| **Regulations:** | **UN 1H2/X295/S**<br>**DOT 49 CFR 173.3** |