Mc MINING GROUPE PICHORI Quality First

LEADER IN INDUSTRIAL TOOLS & EQUIPMENT

Technical sheet



Weblift - Standard Flat Slings - 3 TONNE

Marque: UNITEX MILLER - UK

Ref Product: wire:MCC090

Ref Mcmining: SANGW3TX--------

Description	
Weblift - Standard Flat Slings - 3 TONNE Manufactured from 100% polyester fibres (PES). Our lifting slings are a more versatile solution than substitute products such as wire rope or chain options. For special applications. - Woven from high tenacity polyester (PES) yarn - STRIPE DENOTES SWL - Colour coded for easy identification - Off the shelf product available up to 6T (standard) Custom made solutions for non standard applications - Available with a choice of wear sleeves for added protection at the load points. Woven from high tenacity polyester yarn, these slings feature low weight, flexibility of use and ease of handling. They give significant improvements in safety and costs in comparison to other lifting equipment.	
Technical specification	
Color code	MC90 3T
WLL (working load limit)	3 TONNE
Webbing width (mm)	90
Thickness (mm)	7.5
Eye length 1m effective length in mm (L2)	250
Eye length 2m effective length in mm (L2)	400
Eye length 3m effective length in mm (L2)	-
Standard eye type	3
Weight 1m (kg) L2	0.71
Weight 2m (kg) L2	1.25
Weight 3m (kg) L2	1.8
Weight (kg) per 1m extra EWL (Effective Working Length)	0.55

Products ranges		
References	**REF MC MINING**	**EWL (Effective Working Length)**
MCC09003	**SANGW3TX3M-MILLER**	3m
MCC09004	**SANGW3TX4M-MILLER**	4m
MCC09006	**SANGW3TX6M-MILLER**	6m

Certification
- MANUFACTURED AS STANDARD IN ACCORDANCE TO EN1492-1 **- ISO 9001 - 2015**
MADE IN UK