Mc MINING GROUPE PICHORI Quality First

LEADER IN INDUSTRIAL TOOLS & EQUIPMENT

# Technical sheet



**Miniature circuit breaker (MCB), Easy9, 1P+N, 25A, C curve, 6000A**

Marque: SCHNEIDER ELECTRIC

Ref Product: wire:SCEZ9P35625

Ref Mcmining: SCEZ9P35625

| DESCRIPTION | |
|---|---|
| **Miniature circuit breaker (MCB), Easy9, 1P+N, 25A, C curve, 6000A (IEC/EN 60898-1)** | |
| **EZ9P35625** | |
| **It is a 1P+N circuit breaker with 1 protected pole** | |
| **In rated current** | 25A |
| **tripping curve.** | C |
| **Icn rated short circuit breaking capacity** | up to 6000A at 230VAC conforming to IEC 60898-1 standard. |
| **Standard** | **compliant with IEC 60898-1 standard.** |
| **protection against** | short circuit |
| **protection of cable against** | overloads. |
| **fault tripping indication on the front panel by the position of the handle** | (O-I engraved). |
| **dedicated for** | residential and small commercial buildings. |
| **electrical endurance** | up to 4000 cycles |
| **mechanical endurance** | going up to 10000 cycles. |
| **Ue operational voltage** | 230VAC. |
| **Uimp rated impulse withstand voltage** | 4kV. |
| **operating frequency** | 50Hz. |
| **can be mounted on** | DIN rail for modular installation. |
| **width** | 2 pitches of 9mm. |
| **dimensions** | (W) 18mm x (H) 81mm x (D) 78mm. |
| **degree of protection** | IP20 According to IEC 60529 standard / IP40 in enclosure. |
| **operating temperature** | -25°C to 60°C. |
| **storage temperature** | -40°C to 85°C. |