# Technical sheet




**ABC dry chemical powder fire extinguishers 6KG**

Marque: LX FIRE

Ref Product: wire:LX04-08

Ref Mcmining: LX04-08

| **Description** | |
|---|---|
| ABC dry chemical powder fire extinguishers 6KG<br>LX04-08 | |
| **ABC CHARACTERISTICS** | ABC dry chemical powder fire extinguishers are suitable for use on :<br>Class A (ordinary solids),<br>Class B fires (flammable liquids) and<br>Class C (gas and vapors) fires.<br><br>The ABC type Portable Gas Cartridge Type fire extinguishers can also be used on electrically actuated fires. |
| **PRODUCT FEATURES** | - Easy and ergonomic during use<br>- Fast and effective during extinguishing<br>- Economical in maintenance and service. - The shut-off valve with pressure indicator enhances extinguisher control. - The valve design allows for temporary interruption during extinguishing. - Refillable multiple times<br>- The extinguisher tank is coated with UV-resistant polyester paint<br>- |
| **QUALITY AND SAFETY** | The product is manufactured in compliance with international and EU market requirements, based on the ISO 9001 certified quality system.<br>- It meets the requirements of the European standard EN3 and the Safety Directives PED 2014/68/EU.<br><br>**CERTIFICATE N° :**<br>**N°/15/CN/3808-6**<br>**- N° /11/CN/2416-5**<br>**- 06/03/2023**<br>**- CE 0062**<br>**- APRAGAZ B**<br>**- EN 3-7**<br>**- CE - EN1866-2 (2014)** |
| **TECHNICAL SPECIFICATION** | |
| **DESCRIPTION** | 6KG ABC |
| **CODE** | LX04-08 |
| **AGENT** | ABC DRY CHEMICAL POWDER 40 |
| **PROPELLANT** | DRY AIR |
| **MATERIAL** | ST12 |
| **VALVE** | M30x1.9 |
| **WORKING PRESSURE** | 14bar at 20°C |
| **MAX WORKING PRESSURE** | 18Bar |
| **TEST PRESSURE** | 27Bar |
| **FIRE CLASS** | ABC |

| | |
|---|---|
| **DISCHARGE TIME** | >8s |
| **EXTINGUISHER WEIGHT** | 8.9kg |
| **OPERATING TEMPERATURE** | -30°C - +60°C |
| **CYLINDER SIZE (mm)** | 162x420 |
| **PACKING SZE (mm)** | 175x175x525 |