Mc MINING GROUPE PICHORI Quality First

LEADER IN INDUSTRIAL TOOLS & EQUIPMENT

# Technical sheet



**ABC dry chemical powder fire extinguishers 50KG**

Marque: LX FIRE

Ref Product: wire:LX06-03

Ref Mcmining: LX06-03

| **Description** | |
|---|---|
| ABC dry chemical powder fire extinguishers 50KG<br>LX06-03 | |
| **ABC CHARACTERISTICS** | ABC dry chemical powder fire extinguishers are suitable for use on :<br>Class A (ordinary solids),<br>Class B fires (flammable liquids) and<br>Class C (gas and vapors) fires.<br><br>The ABC type Portable Gas Cartridge Type fire extinguishers can also be used on electrically actuated fires. |
| **PRODUCT FEATURES** | - Easy and ergonomic during use<br>- Fast and effective during extinguishing<br>- Economical in maintenance and service<br>- The shut-off valve with pressure indicator enhances extinguisher control<br>- The valve design allows for temporary interruption during extinguishing<br>- Refillable multiple times<br>- The extinguisher tank is coated with UV-resistant polyester paint<br>- |
| **QUALITY AND SAFETY** | The product is manufactured in compliance with international and EU market requirements, based on the ISO 9001 certified quality system.<br>- It meets the requirements of the European standard EN3 and the Safety Directives PED 2014/68/EU.<br><br>**CERTIFICATE N° :**<br><br>**N°/15/CN/3808-6**<br>**- N° /11/CN/2416-5**<br>**- 06/03/2023**<br>**- CE 0062**<br>**- APRAGAZ B**<br>**- EN 3-7**<br>**- CE - EN1866-2 (2014)** |
| **TECHNICAL SPECIFICATION** | |
| **DESCRIPTION** | 50KG ABC |
| **CODE** | LX06-03 |
| **AGENT** | ABC DRY CHEMICAL POWDER 40 |
| **PROPELLANT** | DRY AIR |
| **MATERIAL** | Q235B |
| **VALVE** | G2 PRESSURE RELIEF |
| **WORKING PRESSURE** | 14bar at 20°C |
| **MAX WORKING PRESSURE** | 18Bar |

| | |
|---|---|
| **TEST PRESSURE** | 35Bar |
| **FIRE CLASS** | ABC |
| **DISCHARGE TIME** | >14s |
| **EXTINGUISHER WEIGHT** | 77.22kg |
| **OPERATING TEMPERATURE** | -30°C - +60°C |
| **CYLINDER SIZE (mm)** | 320x850 |
| **PACKING SZE (mm)** | 500x480x1150 |