Mc MINING GROUPE PICHORI Quality First

LEADER IN INDUSTRIAL TOOLS & EQUIPMENT

Technical sheet



BESTBOY S3 All-time favorite, mid-cut safety shoe

Marque: SAFETY JOGGER - BELGIUM

Ref Product: wire:CHABESTBOYS3---

Ref Mcmining: CHABESTBOYS3---

PRODUCT DESCRIPTION

BESTBOY S3
All-time favorite, mid-cut safety shoe
All-time favorite, mid-cut safety shoe, with all features of the original bestboy in an updated design.

Oil & fuel resistant
The outsole is resistant against oil and fuel.

S3
S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons.
These shoes also protect against perforation risk of the sole, and foot crushing.

SRC slip resistant
soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.

Steel toecap
Robust metal support to protect the feet of the wearer against falling or rolling objects.

Steel midsole
Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetrating the outsole.

Breathable leather upper
Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.

MADE IN BELGIUM

TECHNICAL SPECIFICATION

DESCRIPTION		RESULT	EN ISO 20345
Upper: Barton Action Leather			
	Upper: permeability to water vapor	2.2 mg/cm²/h	? 0.8
	Upper: water vapor coéfficient	25 mg/cm²	? 15
Lining: Mesh			
	Lining: permeability to water vapor	49.8 mg/cm²/h	? 2
	Lining: water vapor coéfficient	398.8 mg/cm²	? 20
Footbed: SJ foam			
	Footbed: abrasion resistance (dry/wet) (cycles)	25600/12800 Cycles	25600/12800
Midsol: Steel			
Outsol: PU/PU			

	Outsole abrasion resistance (volume loss)	56.4 mm³	? 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	0.44 friction	? 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	0.41 friction	? 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	0.29 friction	? 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	0.29 friction	? 0.22
	Antistatic value	120.7 MegaOhm	0.1 - 1000
	ESD value	N/A MegaOhm	0.1 - 100
	Heel energy absorption	29 J	? 20
Toecap: Steel			
	Impact resistance toecap (clearance after impact 200J)	15 mm	? 14
	Compression resistance toecap (clearance after compression 15kN)	15 mm	? 14

Category

S3 / SR, SC, LG, CI, FO

Sample weight

0.690 kg

Norms

ASTM F2413:2018
EN ISO 20345:2022+A1:2024

INDUSTRIE

Construction, Automotive, Chemical, Cleaning, Logistics, Oil & Gas, Industry

ENVIRONMENTS

Dry environment, Muddy environment, Uneven surfaces, Wet environment

Size range

Ref Mc Mining	Size
CHABESTBOYS3-35	35
CHABESTBOYS3-36	36
CHABESTBOYS3-37	37
CHABESTBOYS3-38	38
CHABESTBOYS3-39	39
CHABESTBOYS3-40	40
CHABESTBOYS3-41	41
CHABESTBOYS3-42	42
CHABESTBOYS3-43	43
CHABESTBOYS3-44	44
CHABESTBOYS3-45	45
CHABESTBOYS3-46	46
CHABESTBOYS3-47	47
CHABESTBOYS3-48	48