# Technical sheet



**Safety Shower & Eye Washer Model:SS-S100**

Marque:

Ref Product: wire:EXTDOUCSS-S100

Ref Mcmining: EXTDOUCSS-S100

| **Description** | |
|---|---|
| The combination safety shower & eyewash unit saves space and fits easily into any work environment,allow workers to flush away hazardous substances that can cause injury. The shower valve operates quickly by a pull rod with a round handle. Shower provides a superior washdown with a more even spray pattern. Eyewash operated by a large, attractive push handle. safe, steady water flow under varying water supply conditions from 0.2-0.8 Mpa is assured by integral flow control valve assembly. | |
| **Technical Details:?** | |
| **Material:** | 304 Stainless Steel |
| **Shower Head/Bowl:** | 304 Stainless Steel |
| **Shower Handle:** | 304 Stainless Steel |
| **Spray Head:** | ABS plastic in safety yellow color |
| **Valve:** | Shower valve is making of 1" SS ball valve.<br>Eyewasher valve is making of 1/2"SS ball valve |
| **Pedestal:** | 304 Stainless Steel |
| **Foot treadle:** | 304 Stainless Steel |
| **Flow Valve build in to avoid secondary hurt** | |
| **Water working pressure:** | 0.2MPA-0.8MPA |
| **Flow control:** | 76L/Min |
| **Standard:** | **EN 15154-1&2:2006, AS 4775:2007, ANSI Z358.1-2014** |
| **Gross Weight:** | 18.8KGS,Net Weight:17.5KGS |
| **Dimension:** | 91cm*41cm*30cm |